

BY-PASS JUMPERS



We offer a full range of By-Pass Jumpers for use on systems up to 35kV. Handle Clamps are available in yellow, impact resistant, modified polyolefin material or clear, high impact polycarbonate. Both having moulded in Grip Tabs and Hand Guard for easy use with Rubber Gloves. Alternatively Jumper Cable can be fitted with Duckbill type Clamps for installation and removal by Hot Stick.

LOW VOLTAGE BY-PASS JUMPERS

LV By-Pass Jumpers can be ordered with Yellow or Clear Handles. Cable has highly flexible, tinned copper strands with double insulation EPR-CSP sheath. 35 Sq.mm cable with a 225 Amp Continuous Current rating is offered as standard, but other sizes are available on request. Standard lengths are 2 metre, 4 metre and 6 metre but we can make up cable lengths to your individual requirements.

CAT. NO.	LENGTH	HANDLE TYPE
LV-BPJ-2MY	2 Metre	Yellow
LV-BPJ-2MCL	2 Metre	Clear
LV-BPJ-4MY	4 Metre	Yellow
LV-BPJ-4MCL	4 Metre	Clear
LV-BPJ-6MY	6 Metre	Yellow
LV-BPJ-6MCL	6 Metre	Clear



Clear Handle Option allows easy inspection of Cable to Ferrule crimp connection.



HIGH VOLTAGE BY-PASS JUMPERS

Available for installation by Rubber Glove or Hot Stick Method we can assemble By-Pass Jumpers to your requirement. 15kV By-Pass Jumper cable is available in 200, 260 and 300 Amp ratings. 25kV and 35kV By-Pass Jumpers also available on request. Duckbill Clamps can be provided with threaded terminal or pressure type terminal.



Tel: 01275 342700/Fax: 01275 349009
E-mail: enquiries@horizon.com

A9
05/06