

FIBREGLASS EXTENSION LADDERS



Tested and Approved to BS EN 131, our range of Fibreglass Ladders are designed for industrial applications and offer strength, safety and durability and are ideally suited to any area where there is a possibility of electrical hazard. The Ladders feature non-conductive, fibreglass side rails which have excellent insulation properties. All Ladders have large D shaped Aluminium Rungs, positioned at the correct working angle for maximum comfort.

As standard, Ladders come with swivel type safety feet with slip resistant tread. Uniquely our Ladder Rungs are joined to large Aluminium Plates and are riveted to the side rails. This allows any damaged Rungs to be replaced easily, avoiding costly replacement of the complete Ladder. All Ladders are side rope operated with a "fail-safe" pressed steel Rung-lock mechanism. A choice of leather or swivel Pole Grips are available for use on Poles or Lighting Columns. Round Feet and Shrouded Fly Rungs can be ordered as added extras. Ladders are rated at Maximum Permissible Load 150Kg.

FEATURES



Riveted D Rungs are easily replaced if damaged.



Ladders are side Rope Operated with Tufnol Pulleys and have "Fail-Safe" type operation.



OPTIONS



Leather Pole Grip made of flexible high strength nylon reinforced chrome leather.



One or Two Shrouded Rungs can be ordered as an added extra.



Swivel Feet fitted as standard.



Round Feet with rubber tread available as alternative.

CAT. NO.	LENGTH EACH SECTION	MAX. EXT. LENGTH	APPROX. WEIGHT
FG216	2.4M (8')	4.0M (13')	16kg
FG220	3.0M (10')	5.2M (17')	21kg
FG224	3.6M (12')	6.4M (21')	25kg
FG228	4.3M (14')	7.7M (25')	28kg
FG232	4.8M (16')	8.9M (29')	34kg

**SINGLE SECTION LADDERS
AVAILABLE ON REQUEST**

Tel: 01275 342700/Fax: 01275 349009
 E-mail: enquiries@hor-i-zon.com

D2
02/05