

SLINGS & SHACKLES



ROUND SLINGS

Nylon Round Slings are offered in a range of sizes and capacities. Universal colour coding ensures correct Safe Working Load. Manufactured from high quality Polyester these heavy duty Slings are ideal for a harsh working environment. All Slings are supplied with a Certificate of Conformity.

Rated Capacities For Round Slings								
Working load limit for each sling in basic configuration	Colour Coding	Available lengths periphery	Straight Pull M* = 1	Choke Hitch M* = 0.8	Basket Hitch Parallel M* = 2	Basket Hitch 90° M* = 1.4	Two Leg Sling Max 90° M* = 1.4	4 Leg Sling Max 90° M* = 2
1.0	Violet	1 to 32 metres	1.0	0.8	2.0	1.4	1.4	2.0
2.0	Green	1 to 32 metres	2.0	1.6	4.0	2.8	2.8	4.0
3.0	Yellow	1 to 32 metres	3.0	2.4	6.0	4.2	4.2	6.0
4.0	Grey	1 to 32 metres	4.0	3.2	8.0	5.6	5.6	8.0
5.0	Red	1 to 32 metres	5.0	4.0	10.0	7.0	7.0	10.0
6.0	Brown	2 to 32 metres	6.0	4.8	12.0	8.4	8.4	12.0
8.0	Blue	2 to 32 metres	8.0	6.4	16.0	11.2	11.2	16.0
10	Orange	2 to 32 metres	10.0	8.0	20.0	14.0	14.0	20.0


M = Mode Factor Factor of Safety for all webbing Slings = 7 : 1
 Working Load Limit (WLL) = Sling Rating x Mode Factor

SHACKLES

Large and Small Dee and Bow Shackles in a wide range of sizes.

SMALL DEE SHACKLES

SWL TONNES	Ins.	B mm	Ins.	C mm	Ins.	D mm
0.30	3/8	9.5	3/8	9.5	7/8	22.1
0.60	1/2	12.7	5/8	15.8	1 3/8	34.9
1.00	5/8	15.8	7/8	22.1	1 7/8	47.5
1.75	3/4	19	1	25.4	2 1/4	57.1
2.50	7/8	22.1	1 1/4	31.7	2 3/4	69.8




LARGE DEE SHACKLES

SWL TONNES	Ins.	B mm	Ins.	C mm	Ins.	D mm
0.25	3/8	9.5	1/2	12.7	1	25.4
0.50	1/2	12.7	3/4	19	1 1/2	38.1
0.75	5/8	15.8	1 1/8	28.6	2 1/8	54
1.50	3/4	19	1 1/4	31.7	2 1/2	63.5
2.00	7/8	22.1	1 1/2	38.1	2 7/8	72.9

SMALL BOW SHACKLES

SWL TONNES	Ins.	B mm	Ins.	C mm	Ins.	D mm
0.20	3/8	9.5	1/2	12.7	1	25.4
0.50	1/2	12.7	5/8	15.8	1 1/2	38.1
1.00	5/8	15.8	7/8	22.1	2	50.8
1.50	3/4	19	1 1/8	28.6	2 1/2	63.5
2.00	7/8	22.1	1 3/8	34.9	3	76.2



LARGE BOW SHACKLES

SWL TONNES	Ins.	B mm	Ins.	C mm	Ins.	D mm
0.15	3/8	9.5	1/2	12.7	1 1/8	28.6
0.45	1/2	12.7	5/8	15.8	1 5/8	41.2
0.75	5/8	15.8	7/8	22.1	2 1/8	54
1.25	3/4	19	1 1/8	28.6	2 3/4	69.8
2.00	7/8	22.1	1 3/8	34.9	3 3/8	85.7

Tel: 01275 342700/Fax: 01275 349009
 E-mail: enquiries@hor-i-zon.com