

# ACCESSORIES FOR LV FUSE UNITS



Designed for use with Henley and Lucy LV fuse units, Horizon offer the following recently developed products.



## FUSE REMOVAL TOOLS

Developed to allow removal and insertion of the Fuse Carrier on Henley and Lucy fuse units from the ground, the 34031-FRSRT is used for loosening and tightening the nylon retaining screws for which this adapter has been specially profiled. The EX3-699 Clamp is used to grip the handle to remove and insert the Fuse Carrier. Both tools can be fitted directly onto the top section of a Telescopic Rod or adapted to fit Slot Together Operating Rods. Ideal for use by engineers in storm conditions or anytime where safety demands operations should not be carried out in close proximity



34031-FRSRT EX3-699

## TERMINAL SHROUD FOR HENLEY & LUCY LV FUSE UNIT



The Terminal Shroud provides protection where the cover has been removed from the fuse unit. The Shroud insulates the live terminal and cable end allowing work to be carried out safely on the other terminal. The Shroud is available for the left or right terminal for both the Henley and Lucy fuse units.

PART NO.	DESCRIPTION
PML3010	Left Side Terminal Shroud for Henley fuse unit
PML3009	Right Side Terminal Shroud for Henley fuse unit
PML3014	Left Side Terminal Shroud for Lucy fuse unit
PML3015	Right Side Terminal Shroud for Lucy fuse unit

## LV FUSE INSULATED JUMPER HANDLE

The Insulated Jumper Handle has been designed to slot over and tighten onto the terminal fork on a Henley or Lucy fuse unit. Tested for continuous current at 400 Amps, the brass clamping jaws have a self aligning screw which ensures that the handle cannot be inadvertently dislodged once the clamp has been tightened onto the terminal. Applications include two handles with double insulated cable for jumpering between fuse units, single handle with double insulated cable and lug for connecting to a generator or single handle with orange Aluflex cable for earthing a fuse unit. Handles are colour coded, yellow, red and blue phase colours or grey for earthing applications.



Tel: 01275 342700/Fax: 01275 349009  
 E-mail: [enquiries@hor-i-zon.com](mailto:enquiries@hor-i-zon.com)